

POWERCHOCK 3

PORTABLE WHEEL RESTRAINT SYSTEM



PROTECT YOUR LOADING DOCK PERSONNEL

POWERCHOCK 3 is an easy-to-handle wheel restraint system, highly suitable for narrow spaces between loading docks, providing outstanding value.





EXCLUSIVE



WARRANTY

- RUGGED**
- RELIABLE**
- EASY-TO-HANDLE**



QUALITY & ROBUSTNESS



WINTER RESISTANT



LOWEST TCO



UNIVERSALLY COMPATIBLE



ALL GROUNDS & SPACES




RAPID & INTUITIVE

TECHNICAL SPECIFICATIONS

POWERCHOCK 3

- High-tensile steel wheel chock linked to a control box via communication cable installed on a flexible pole.
- Three sections (totalling 12 feet) of hot-dip, galvanized steel, ground-fixed restraining plate, in the dock bay area.
- 2 sensors linked to an audiovisual communication system:
 - Equipped with wheel sensor inside chock to confirm proper wheel chock placement
 - Dock sensor to confirm star and completion of loading
- Communication system equipped with indoor control box, visual indicators (red/green LED lights), and audible alarm. "Chock engaged" indicator light and self-diagnostic function included. Also equipped with exterior LED traffic lights and an audible alarm.
- For easier handling by the driver, the trolley is an available option. "Chock engaged" indicator light and self-diagnostic function included. Also equipped with exterior LED traffic lights and an audible alarm.



Height	15 ³ / ₄ in
Length	21 ¹ / ₄ in
Width	6 in
Weight	28.6 lbs

Additional heights and widths available.

DETAILS & VIDEOS AVAILABLE HERE

